

## Claims

Cancel Claim 24.

Amend Claims 1, 18, 21, 23 and 25.

1. **(Currently Amended)** A pod latchdown mechanism for latching a control pod to a subsea oilfield structure having control lines extending to a coupler component supported on a receptacle plate on the subsea oilfield structure for cooperation with a coupler component supported on a lower mounting plate on the control pod, the control pod including a pod housing defining a pod chamber therein, the latchdown mechanism comprising:

a subsea receptacle housing secured to the subsea structure for receiving the control pod therein and having a latching surface at an upper end of the receptacle housing above the pod chamber when the coupler components are mated;

a latchdown actuator movably supported on the control pod; and

a plurality of gripping arms for engagement and disengagement with the latching surface to selectively connect and disconnect the control pod from the oilfield structure in response to movement of the latchdown actuator.

2. **(Original)** A latchdown mechanism as defined in Claim 1, further comprising:

the latching surface on the receptacle housing includes at least one recess in an inner surface of the receptacle housing for receiving the plurality of gripping arms.

3.     **(Original)** A latchdown mechanism as defined in Claim 1, wherein the latchdown actuator is movable along a central axis substantially coaxially with a control pod central axis.

4.     **(Original)** A latchdown mechanism as defined in Claim 1, wherein the latchdown actuator comprises a collar movable between an unlatched position and a latched position and pivotally connected to the plurality of gripping arms, thereby moving the plurality of gripping arms into and out of engagement with the latching surface on the receptacle housing.

5.     **(Original)** A latchdown actuator as defined in Claim 4, further comprising:  
a hydraulically powered running tool for moving the collar between the latched and unlatched positions.

6.     **(Original)** A latchdown mechanism as defined in Claim 4, further comprising:  
an upwardly extending sleeve secured to the control pod for guiding movement of a collar.

7.     **(Original)** The latchdown mechanism as defined in Claim 6, wherein each of the gripping arms lies with the plane substantially perpendicular to a central axis of the control pod when in the latched position.

8.     **(Original)** A latchdown mechanism as defined in Claim 6, further comprising:

a ring carrier assembly radially outward of the sleeve and including a split ring for securing the plurality of gripping arms in engagement with the latching surface on the receptacle housing.

9. **(Original)** A latchdown mechanism as defined in Claim 8, further comprising:

the sleeve includes an internal sleeve groove; and

the split ring is received within the sleeve groove when the gripping arms are in engagement with the latching surface.

10. **(Original)** A latchdown mechanism as defined in Claim 8, further comprising:

a shear member for interconnecting the ring carrier assembly with the collar, such that the shear member may shear to release the collar from the ring carrier assembly to move the plurality of gripping arms out of engagement with the latching surface.

11. **(Original)** A latchdown mechanism as defined in Claim 1, further comprising:

one of the control pod and the receptacle housing being provided with an axially extending slot having a radial thickness sized to receive a protrusion on the other of the control pod and the receptacle housing for rotationally aligning the control pod with respect to the receptacle housing prior to activating the latchdown mechanism.

12. **(Original)** A latchdown mechanism as defined in Claim 1, further comprising:

a locking mandrel on a running tool axially movable with respect to a running tool head from an unlocked position to a locked position, such that the running tool head is selectively secured to the control pod;

a sleeve secured to the pod and having a central bore for receiving the running tool head; and

one or more locking members radially movable with respect to the running tool head in response to axial movement of the locking mandrel to lock the running tool head to the sleeve.

13. **(Original)** A latchdown mechanism as defined in Claim 12, further comprising:

a crank mechanism for controlling axial movement of the locking mandrel with respect to the running tool head.

14. **(Original)** A latchdown mechanism as defined in Claim 12, wherein the locking mandrel is a hydraulically powered piston movable from an unlocked position to a locked position.

15. **(Original)** A pod latchdown mechanism for latching a control pod and related control lines to a subsea oilfield structure, the latchdown mechanism comprising:

a subsea receptacle housing secured to the subsea structure and having a latching surface including at least one recess in an inner surface of the receptacle housing;

a collar movable between an unlatched position and a latched position, thereby moving a plurality of gripping arms into and out of engagement with the latching surface of the receptacle housing; and

the plurality of gripping arms are positioned along a periphery of the control pod for engagement and disengagement with the latching surface to selectively connect and disconnect the control pod from the oilfield structure in response to movement of the collar.

16. **(Original)** A latchdown mechanism is defined in Claim 15, further comprising:

one of the control pod and the receptacle housing being provided with an axially extending slot having a radial thickness sized to receive a protrusion on the other of the control pod and the receptacle housing for rotationally aligning the control pod with respect to the receptacle housing prior to activating the latchdown mechanism.

17. **(Original)** A latchdown mechanism as defined in Claim 15, further comprising:

an upwardly extending sleeve secured to the control pod for guiding movement of the collar; and

each of the plurality of gripping arms are pivotally mounted to the collar and to the control pod at a position radially outward of the collar.

18. **(Currently Amended)** A pod latchdown mechanism for latching a control pod to a subsea oilfield structure, the control pod including a pod housing having an upper pod member defining a pod chamber below the upper pod

member, the latchdown mechanism comprising:

a subsea receptacle housing secured to the subsea structure for receiving the control pod therein;

a latchdown actuator movably supported on the control pod; and

a plurality of gripping arms positioned along a periphery of the control pod for selective engagement and disengagement with the receptacle housing above the upper pod member when the control pod is landed in the subsea oilfield structure, the plurality of gripping arms being pivotally connected to the control pod such that movement of the latchdown actuator to an unlatched position produces a decoupling force between the control pod and the subsea structure greater than an unlatching force of the latchdown actuator.

19. **(Original)** A latchdown mechanism as defined in Claim 18, further comprising:

the subsea receptacle housing has a cavity therein to receive the control pod extending axially over substantially the entire length of the control pod, the receptacle housing including an inner profile to latch the control pod to the subsea structure in response to movement of the latchdown actuator with respect to the control pod.

20. **(Original)** A latchdown mechanism as defined in Claim 18, further comprising:

one of the control pod and the receptacle housing being provided with an axially extending slot having a radial thickness sized to receive a protrusion on the other of the control pod and the receptacle housing for rotationally aligning the control pod with respect to the receptacle housing prior to activating the latchdown mechanism.

21. **(Currently Amended)** A pod latchdown mechanism for latching a control pod with a control pod central axis to a subsea oilfield structure having control lines extending through a receptacle plate on the subsea oilfield structure for cooperation with control lines extending through a lower mounting plate on the control pod, the latchdown mechanism comprising:

a subsea receptacle housing secured to the subsea structure for receiving the control pod therein and having an interior latching surface at an upper end of the receptacle housing;

a latchdown actuator supported on the control pod;

a plurality of gripping arms positioned along a periphery of the control pod for engagement and disengagement with the latching surface to selectively connect and disconnect the control pod from the oilfield structure in response to the latchdown actuator; ~~and~~

an upwardly extending sleeve secured to the control pod for guiding movement of a collar;

each of the plurality of gripping arms are pivotally mounted to the collar and to the control pod at a position radially outward of the collar; and

one of the control pod and the receptacle housing being provided with an axially extending slot having a radial thickness sized to receive a protrusion on the other of the control pod and the receptacle housing for rotationally aligning the control pod with respect to the receptacle housing prior to activating the latchdown mechanism.

22. **(Original)** A latchdown mechanism as defined in Claim 21, further comprising:

the latching surface on the receptacle housing includes at least one

recess in an inner surface of the receptacle housing for receiving the plurality of gripping arms.

23. **(Currently Amended)** A latchdown mechanism as defined in Claim 21, wherein the ~~latchdown actuator comprises a collar~~ is movable between an unlatched position and a latched position, thereby moving the plurality of gripping arms into and out of engagement with the latching surface on the receptacle housing.

24. **(Cancelled)**

25. **(Currently Amended)** A latchdown mechanism as defined in Claim ~~[[1]]~~21, further comprising:

a locking mandrel axially movable with respect to a tool head from an unlocked position to a locked position, such that the tool head is selectively secured to the control pod;

~~a~~the sleeve ~~secured to the pod and~~ having a central bore for receiving the tool head; and

one or more locking members radially movable with respect to the tool head in response to axial movement of the locking mandrel to lock the tool head to the sleeve.

26. **(Original)** A latchdown mechanism as defined in Claim 21, wherein the plurality of gripping arms are pivotally connected to the control pod such that movement of the latchdown actuator to an unlatched position produces a decoupling force between the control pod and the subsea structure greater than an unlatching force of the latchdown actuator.